

Scalable and flexible C&I all-in-one energy storage solution

- ✓ Faster installation time and lower commissioning cost
- ✓ Scalable and flexible deployment
- ✓ Enhanced protection, longer lifespan, and stable operation
- ✓ Flexible, intelligent energy optimization with microgrid compatibility

The GoodWe ESA Series introduces a new, all-in-one Energy Storage System (ESS) tailored for a wide range of Commercial and Industrial (C&I) applications. Featuring a modular design, the ESA Series enables flexible system expansion, streamlined transportation and installation, and simplified operations and maintenance (O&M). Engineered with multi-level protection and advanced safety features—including thermal management at the cell level—the system ensures reliable performance. Its intelligent hybrid cooling approach combines air cooling at the Power Conversion System (PCS) level with smart liquid cooling for the battery modules, all within an IP54-rated enclosure suitable for outdoor environments.

Equipped with integrated Energy Management System (EMS) functionality, the ESA Series supports parallel operation with grid-tied inverters for adaptable C&I deployments. Additionally, when paired with the upcoming GoodWe STS Box, it can operate in off-grid mode with grid-forming capability and Virtual Synchronous Generator (VSG) functionality.



Supports up to 15 units in parallel
(1.87MW/3.91MWh)



3S Coordination with self-developed
PCS, BMS & EMS



AI-driven battery diagnosis
and health prediction



Pack-level humidity monitoring with
auto-dehumidification

Technical Data

GW125/261-ESA-LCN-G10

Battery Data

| | |
|------------------------------------------------|------------------------------|
| Cell Type | LFP (LiFePO4) |
| Cell Capacity (Ah) | 314 |
| Module Nominal Energy (kWh) | 52.25 |
| Number of Packs | 5 |
| Rack Nominal Energy (kWh) | 261.25 |
| Rack Usable Energy (kWh) | 261.25 |
| Nominal Voltage (V) | 832 |
| Operating Voltage Range (V) | 676 ~ 936 |
| Max. Continuous Charge / Discharge Current (A) | 188 |
| Max. Charge / Discharge Current (A) | 198.5 |
| Max. Charge / Discharge Rate | 0.5P |
| Depth of Discharge | 90% ~ 100% (90% Recommended) |

AC Output Data (On-grid)

| | |
|-----------------------------------------------------|------------------------------|
| Nominal Output Power (kW) | 125 |
| Max. Output Power (kW) | 137.5@400V AC; 130.6@380V AC |
| Nominal Apparent Power (kVA) | 125 |
| Nominal Apparent Power Output to Utility Grid (kVA) | 125 |
| Nominal Apparent Power from Utility Grid (kVA) | 125 |
| Max. Apparent Power (kVA) | 137.5@400V AC; 130.6@380V AC |
| Max. Apparent Power Output to Utility Grid (kVA) | 137.5@400V AC; 130.6@380V AC |
| Max. Apparent Power from Utility Grid (kVA) | 137.5@400V AC; 130.6@380V AC |
| Nominal Output Voltage (V) | 400 / 380, 3L / N / PE |
| Output Voltage Range (V) | 340 ~ 440 / 323 ~ 418 |
| Nominal AC Grid Frequency (Hz) | 50 / 60 |
| AC Grid Frequency Range (Hz) | 47.5 ~ 52.5 / 57.5 ~ 62.5 |
| Max. AC Output Current (A) | 198.5 |
| Max. AC Current Output to Utility Grid (A) | 198.5 |
| Max. AC Current from Utility Grid (A) | 198.5 |
| Nominal Output Current (A) | 180.4@400V AC; 189.9@380V AC |
| Power Factor | ~1 (0.8 lag to 0.8 lead) |
| Max. Total Harmonic Distortion | <3% |

AC Output Data (Off-grid)

| | |
|----------------------------------------------|------------------------------|
| Nominal Output Power (kW) | 125 |
| Max. Output Power (kW) | 137.5@400V AC; 130.6@380V AC |
| Nominal Apparent Power (kVA) | 125 |
| Nominal Output Apparent Power to Grid (kVA) | 125 |
| Nominal Input Apparent Power from Grid (kVA) | 125 |
| Max. Apparent Power (kVA) | 137.5@400V AC; 130.6@380V AC |
| Max. Output Apparent Power to Grid (kVA) | 137.5@400V AC; 130.6@380V AC |
| Max. Input Apparent Power from Grid (kVA) | 137.5@400V AC; 130.6@380V AC |
| Nominal Output Voltage (V) | 400 / 380, 3L / N / PE |
| Output Voltage Range (V) | 340 ~ 440 / 323 ~ 418 |
| Nominal Output Frequency (Hz) | 50 / 60 |
| AC Grid Frequency Range (Hz) | 47.5 ~ 52.5 / 57.5 ~ 62.5 |
| Max. AC Output Current (A) | 198.5 |
| Max. AC Current Output to Grid (A) | 198.5 |
| Max. AC Current from Grid (A) | 198.5 |
| Nominal Output Current (A) | 180.4@400V AC; 189.9@380V AC |
| Power Factor | ~1 (0.8 lag to 0.8 lead) |
| Output THDi (@Linear Load) | <3% |

Efficiency

| | |
|---------------------|-------|
| Max. PCS Efficiency | 98.6% |
| System Efficiency | 92.0% |

Protection

| | |
|-------------------------------------|------------|
| Battery Reverse Polarity Protection | Integrated |
| Anti-islanding Protection | Integrated |
| AC Overcurrent Protection | Integrated |
| AC Short Circuit Protection | Integrated |
| AC Surge Protection | Type II |

General Data

| | |
|-----------------------------------|-------------------------------------------------------------------------------------------------|
| Operation Temperature Range (°C) | -25 ~ +55 |
| Derating Temperature (°C) | 45 |
| Storage Temperature (°C) | -20 ~ +45 (One Month); 0 ~ +35 (One Year) |
| Relative Humidity | 10% ~ 95% |
| Max. Operating Altitude (m) | 4000 (2000 derating) |
| Cooling Method | Pack: Liquid Cooling; PCS: Smart Fan Cooling |
| User Interface | LED, WLAN + APP |
| Communication Protocol | Modbus TCP, Modbus RTU |
| Weight (kg) | 2580 |
| Dimension (W x H x D mm) | 1050 x 2250 x 1400 |
| Noise Emission (dB) | ≤70 |
| Topology | Non-isolated |
| Ingress Protection Rating | IP54 |
| Anti-Corrosion | C4 (C5 optional) |
| Configuration of Safety | Aerosol + water-based fire suppression, explosion-proof fan + explosion-proof plates (optional) |
| Charge / Discharge Switching Time | <60ms |

*: Please visit GoodWe website for the latest certificates.