

Lynx Home U Series

5.4-32.4kWh | Low voltage battery

Lynx Home U Series is a low-voltage lithium battery specially designed for residential applications with superior performance. Compatible with GoodWe ES/EM/SBP inverters, Lynx Home U Series comes with GoodWe one-stop-shop solution saving you considerable time and effort. It can be used flexibly for self-consumption and backup applications with a wide capacity range scalable from 5.4 – 32.4kWh. The installation and commissioning are easier and faster than ever with a simple Plug and Play wiring and module auto recognition during system setup. Meet this highly efficient solution for storing your solar power and use it whenever needed.



Smart Control

- Remote diagnosis & update
- Auto reboot after undervoltage



Friendly & Thoughtful Design

- Auto-recognition modules
- Plug & Play wiring



Superb Safety & Reliability

- Reliable LFP technology with high cycle stability
- IP65 protection for outdoor installation safety



Flexible & Adaptable Applications

- 5.4 – 32.4kWh wide capacity range
- Compatible with GoodWe ES/EM/SBP inverters

Technical Data	LX U5.4-L	2*LX U5.4-L	3*LX U5.4-L	4*LX U5.4-L	5*LX U5.4-L	6*LX U5.4-L
Rated Energy (kWh) ¹	5.4	10.8	16.2	21.6	27.0	32.4
Usable Energy (kWh) ²	4.8	9.6	14.4	19.2	24.0	28.8
Cell Type	LFP (LiFePO4)					
Nominal Voltage (V)	51.2					
Operating Voltage Range (V)	48 ~ 57.6					
Nominal Dis- / Charge Current (A) ³	50	100	100	100	100	100
Nominal Power (kW) ³	2.88	5.76	5.76	5.76	5.76	5.76
Communication	CAN					
Weight (kg)	57	114	171	228	285	342
Dimensions (W x H x D mm)	505 x 570 x 175 (LX U5.4-L)					
Operating Temperature Range (°C)	Charge: 0 ~ +50 / Discharge: -10 ~ +50					
Relative Humidity	0 ~ 95%					
Max. Operating Altitude (m)	2000					
Ingress Protection Rating	IP65					
Mounting Method	Wall Mounted / Grounded					
Standard and Certification	Safety	IEC62619, IEC62040, CEC				
	EMC	CE, RCM				
	Transportation	UN38.3				

*1: Test conditions, cell Voltage 2.5 ~ 3.65V, 0.5C charge & discharge at +25 ±2°C for battery system at beginning life. System Usable Energy may vary with different Inverter.

*2: Test conditions, 90% DOD, 0.5C charge & discharge at +25 ±2°C.

*3: Nominal Dis- / Charge Current and power derating will occur related to Temperature and SOC.

*: Please visit GoodWe website for the latest certificates.